



Материал C45 / Material C45

SIZE	chain pitch mm	drill hole mm	BORE		OD mm	L mm	COUPLING DIMENSIONS					Kg.
			min mm	max mm			C mm	D mm	E mm	A mm	B mm	
3012	9.525	12	13.5	16	45	65	27.2	29.5	6	69	63	0.53
4012	12.7	12	14	22	62	79.4	36	36	7.4	77	72	1.03
4014	12.7	12	14	28	69	79.4	45	36	7.4	84	75	1.43
4016	12.7	13.5	16	32	77	87.4	51.5	40	7.4	92	72	1.85
5014	15.875	14.5	17	35	86	99.7	56	45	9.7	101	85	2.62
5016	15.875	14.5	18	40	96	99.7	64	45	9.7	110	87	3.25
5018	15.875	16	18	45	106	123.5	73.5	45	9.7	122	85	4.20
6018	19.05	20	22	56	127	123.5	89.5	56	11.5	147	105	7.75
6020	19.05	20	24	60	139	123.5	102.5	56	11.5	158	105	9.58
6022	19.05	20	28	71	151	123.5	115	56	11.5	168	117	11.6
8018	20.4	20	32	80	169	141.2	115	63	15.2	190	129	15.1
8020	20.4	20	36	90	185	145.2	125	65	15.2	210	137	18.7
8022	20.4	20	40	100	202	157.2	142	71	15.2	226	137	24.5
10020	31.75	25	45	110	233	178.8	162	80	18.8	281	153	36.5
12018	38.1	35	50	125	256	202.7	173	90	22.7	307	181	48.4
12022	38.1	35	56	140	304	222.7	213	100	22.7	357	181	75.8