



COUPLING DIMENSIONS

TYPE	D	D1	d1	L	C	Pin MxL	Number of pins	Pin No.	Max torque N.m	Max speed r/min	Kg.
	mm	mm	mm	mm	mm						
FCL 90	90	35.5	11	11	3	M8x50	4	1	6	4000	1.7
FCL 100	100	40	11	35.5	3	M10x56	4	2	12	4000	2.5
FCL 112	112	45	13	40	3	M10x56	4	2	18	4000	3.0
FCL 125	125	50	13	45	3	M12x64	4	3	27	4000	4.0
FCL 140	140	63	13	50	3	M12x64	6	3	55	4000	5.6
FCL 160	160	80	15	56	3	M12x64	8	3	118	4000	7.8
FCL 180	180	90	15	63	3	M12x64	8	3	160	3500	10.5
FCL 200	200	100	21	71	4	M18x80	8	4	250	3200	16.2
FCL 224	224	112	21	80	4	M18x80	8	4	400	2850	21.6
FCL 250	250	125	25	90	4	M20x85	8	5	616	2550	31.8
FCL 280	280	140	34	100	4	M20x85	8	5	980	2300	44.0
FCL 315	315	160	41	112	4	M20x85	10	5	1568	2050	58.0
FCL 355	355	180	60	125	5	M30x150	8	6	2460	1800	89.5
FCL 400	400	200	60	125	5	M30x150	10	6	3920	1600	113
FCL 450	450	224	65	140	5	M30x150	12	6	6180	1400	145
FCL 560	560	250	85	160	5	M30x150	14	6	9800	1150	229
FCL 630	630	280	95	180	5	M30x150	18	6	15680	1000	296